

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
Type TL
Tire Size 420/85 R 30
LI/SS 140 A8/B



Dimensions (U/M International standard)

Section Width (mm) 438
Overall Diameter (mm) 1475
Static Loaded Radius (mm) 661
Rolling Circumference (mm) 4393
SRI 700
Rim Rec W 15 L
Rim Alt W 13 ; W 14 L

Applications Vineyard Harvester / Tractor / Sprayer
Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1375	1600	1825	2050	2275	2500
40	1375	1600	1825	2050	2275	2500
30	1475	1715	1955	2195	2435	2675
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1475	1715	1955	2195	2435	2675