

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name AGRIMAX RT 855

Version STANDARD
 Type TL
 Tire Size 460/85 R 30
 LI/SS 145 A8/B



Dimensions (U/M International standard)

Section Width (mm) 475
 Overall Diameter (mm) 1544
 Static Loaded Radius (mm) 682
 Rolling Circumference (mm) 4537
 SRI 725
 Rim Rec W 16 L
 Rim Alt W 14 L ; W 15 L

Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1595	1860	2120	2380	2640	2900
40	1595	1860	2120	2380	2640	2900
30	1710	1990	2270	2550	2830	3105
10 LT	2140	2490	2840	3190	3540	3890
10 HT	1710	1990	2270	2550	2830	3105