

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

Pattern Name AGRIMAX RT 765

Version STANDARD
 Type TL
 Tire Size 600/70 R 30
 LI/SS 152 A8/B



Dimensions (U/M International standard)
 Section Width (mm) 591
 Overall Diameter (mm) 1602
 Static Loaded Radius (mm) 711
 Rolling Circumference (mm) 4774
 SRI 750
 Rim Rec DW 20 B
 Rim Alt DW 18 L ; W 18 L

Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1955	2275	2595	2915	3235	3550
40	1955	2275	2595	2915	3235	3550
30	2090	2435	2775	3120	3460	3800
10 LT	2620	3050	3475	3905	4335	4760
10 HT	2090	2435	2775	3120	3460	3800