

TECHNICAL SPECIFICATION

Applications: Spreader / Harvester
 Description: Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

Pattern Name AGRIMAX TERIS

Version: STANDARD
 Type: TL
 Tire Size: 800/65 R 32 CHO
 LI/SS: 178 A8/175 B



Dimensions (U/M International standard)

Section Width (mm): 818
 Overall Diameter (mm): 1853
 Static Loaded Radius (mm): 838
 Rolling Circumference (mm): 5587
 SRI: 875
 Rim Rec: DW 27 B
 Rim Alt: DW 25 B ; DH 27 B

Applications: Spreader / Harvester
 Description: Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

LOAD CAPACITY TABLE (kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3175	3660	4485	4900	5455	5865	6420	6900
40	3450	3975	4875	5325	5925	6375	6975	7500
30	3695	4255	5220	5700	6340	6825	7465	8025
15 Cyc.	5695	6560	8045	8790	9780	10520	11510	12375
10 Cyc.	6210	7155	8775	9585	10665	11475	12555	13500