

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
Type TL
Tire Size 460/85 R 38
LI/SS 149 A8/B



Dimensions (U/M International standard)

Section Width (mm) 475
Overall Diameter (mm) 1747
Static Loaded Radius (mm) 785
Rolling Circumference (mm) 5161
SRI 825
Rim Rec W 16 L
Rim Alt W 14 L ; W 15 L

Applications Vineyard Harvester / Tractor / Sprayer
Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1790	2080	2375	2665	2960	3250
40	1790	2080	2375	2665	2960	3250
30	1915	2230	2545	2855	3170	3480
10 LT	2400	2790	3180	3575	3965	4355
10 HT	1915	2230	2545	2855	3170	3480