

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

Pattern Name AGRIMAX RT 765

Version STANDARD
 Type TL
 Tire Size 580/70 R 38
 LI/SS 155 A8/B

Dimensions (U/M International standard)

Section Width (mm) 577
 Overall Diameter (mm) 1827
 Static Loaded Radius (mm) 821
 Rolling Circumference (mm) 5505
 SRI 875
 Rim Rec W 18 L



Applications Vineyard Harvester / Tractor / Sprayer
 Description AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	2135	2480	2830	3180	3530	3875
40	2135	2480	2830	3180	3530	3875
30	2285	2660	3030	3405	3780	4150
10 LT	2860	3325	3795	4260	4730	5195
10 HT	2285	2660	3030	3405	3780	4150