

## TECHNICAL SPECIFICATION

**Applications** Spreader / Harvester  
**Description** Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

**Pattern Name**      **AGRIMAX TERIS**

**Version**                STANDARD  
**Type**                    TL  
**Tire Size**              520/85 R 42  
**LI/SS**                  168 D



**Dimensions (U/M International standard)**

**Section Width (mm)**      516  
**Overall Diameter (mm)**    1951  
**Static Loaded Radius (mm)** 890  
**Rolling Circumference (mm)** 5851  
**SRI**                        925  
**Rim Rec**                 DW 16 L  
**Rim Alt**                 DD 18 L

**Applications** Spreader / Harvester  
**Description** Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

**LOAD CAPACITY TABLE (kg)**

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.8
65	1850	2185	2520	2800	3140	3420	3980	4540	5100	5600	-
50	1945	2295	2650	2940	3295	3590	4175	4765	5355	5880	-
40	2025	2395	2765	3070	3440	3745	4360	4970	5585	6135	-
30	2130	2515	2900	3220	3610	3930	4575	5250	5865	6440	-
25	2195	2590	2990	3320	3720	4055	4715	5380	6045	6640	-
10	2775	3280	3780	4200	4705	5125	5965	6805	7645	8400	-
10 Cyc.	-	-	-	-	-	-	-	-	-	-	9520