

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer
Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
Type TL
Tire Size 380/85 R 30
LI/SS 135 A8/B



Dimensions (U/M International standard)

Section Width (mm) 380
Overall Diameter (mm) 1408
Static Loaded Radius (mm) 633
Rolling Circumference (mm) 4169
SRI 675
Rim Rec W 12
Rim Alt W 11 ; W 13

Applications Vineyard Harvester / Tractor / Sprayer
Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1200	1400	1595	1790	1985	2180
40	1200	1400	1595	1790	1985	2180
30	1285	1495	1705	1915	2125	2335
10 LT	1610	1875	2140	2400	2665	2925
10 HT	1285	1495	1705	1915	2125	2335